

TECHNICAL DATA SHEET: **229**

Validity date: **01 September 2016**

| | | |
|--|--|----------|
| ➤ Product Description: | BOPP adhesive tape | |
| | Acrylic adhesive | |
| | Noisy unwinding | |
| | 'Ecological' solvent-free tape | |
| ➤ Technical Data: | Backing thickness: | 28 µm |
| | Total thickness: | 48 µm |
| | Adhesion to steel: | 2,6 N/cm |
| | Tensile strength: | 45 N/cm |
| | Elongation at break: | 160 % |
| ➤ Application: | Recommended for medium duty boxes with hand dispenser | |
| | Recommended for automatic carton sealing machines | |
| ➤ Warning: | Protect from humidity – Use and store at temperature above 18°C. | |
| ➤ Above mentioned technical data are valid also for the following versions: | ET = easy tear | |
| | J = jumbo | |
| | Data referring to tensile strength and elongation at break cannot be applied to ET version = easy tear | |

Above mentioned figures represent the average values of our regular production; as such, they are not binding. Customer must verify through practical tests that product is fit for the use he intends it for and is responsible for any risk and damage caused by the use of the product. Above mentioned figures have a range of variation +/- 5% and may be changed at any moment for production needs or technical updates.

Test methods: AFERA - PSTC. rev. 1 Fabo