

## TECHNICAL DATA SHEET: 248

Validity date: 01 March 2015

	BOPP adhesive tape	
Product Description:	Acrylic adhesive	
	Silent unwinding (no noise)	
	Excellent initial tack	
	'Ecological' solvent-free tape	
> Technical Data:	Backing thickness:	35 μm
	Total thickness:	63 μm
	Adhesion to steel:	2,8 N/cm
	Tensile strength:	55 N/cm
	Elongation at break:	160 %
> Application:	Recommended for all kind of boxes	
	Recommended for back-side print if supplied with no Corona treatment	
> Warning:	Protect from humidity – Use and store at temperature above 18°C.	
	<b>C</b> = coloured	
	<b>D</b> = back-side print	
	ET = easy tea	
Above mentioned technical data are	<b>J</b> = jumbo	
valid also for the following versions:	P = pre-printed	
	X = pack-roll	
	Data referring to tensile strength and elongation at break cannot be applied to ET version = easy tear	

Above mentioned figures represent the average values of our regular production; as such, they are not binding. Customer must verify through practical tests that product is fit for the use he intends it for and is responsible for any risk and damage caused by the use of the product. Above mentioned figures have a range of variation +/- 5% and may be changed at any moment for production needs or technical updates.

Test methods: AFERA - PSTC. rev. 1 Fabo