

## TECHNICAL DATA SHEET: **250**

Validity date: **01 March 2015**

➤ <b>Product Description:</b>	<b>BOPP</b> adhesive tape	
	Acrylic adhesive	
	Silent unwinding (no noise)	
	'Ecological' solvent-free tape	
➤ <b>Technical Data:</b>	Backing thickness:	50 µm
	Total thickness:	70 µm
	Adhesion to steel:	2,4N/cm
	Tensile strength:	65 N/cm
	Elongation at break:	170 %
➤ <b>Application:</b>	Recommended for heavy duty boxes	
	Recommended for back-side print if supplied with no Corona treatment	
➤ <b>Warning:</b>	Protect from humidity – Use and store at temperature above 18°C.	
➤ <b>Above mentioned technical data are valid also for the following versions:</b>	<b>C</b> = coloured <b>D</b> = back-side print <b>ET</b> = easy tea <b>J</b> = jumbo <b>P</b> = pre-printed	
	Data referring to tensile strength and elongation at break <b>cannot be applied</b> to <b>ET</b> version = easy tear	

Above mentioned figures represent the average values of our regular production; as such, they are not binding. Customer must verify through practical tests that product is fit for the use he intends it for and is responsible for any risk and damage caused by the use of the product. Above mentioned figures have a range of variation +/- 5% and may be changed at any moment for production needs or technical updates.

Test methods: AFERA - PSTC. rev. 1 Fabo