

## TECHNICAL DATA SHEET: **661**

Validity date: **31 March 2017**

|                               |   |                     |
|-------------------------------|---|---------------------|
| ➤ <b>Product Description:</b> | <b>FLAT /THIN PAPER</b> masking tape <b>(YELLOW)</b>                              |                     |
|                               | Acrylic adhesive  |                     |
|                               | <i>'Ecological' solvent-free tape</i>   |                     |
| ➤ <b>Technical Data:</b>      | Backing weight:   | 50 g/m <sup>2</sup> |
|                               | Total thickness:  | 90 μm               |
|                               | Adhesion to steel:  | 0,8 N/cm            |
|                               | Tensile strength:   | 30 N/cm             |
|                               | Elongation at break:  | 5 %                 |
| ➤ <b>Application:</b>         | Recommended for indoor and outdoor masking applications                           |                     |
|                               | High grade masking for precise and flat edges; also suitable on delicate surfaces |                     |
|                               | Due to its water repellency can be used with water-based paints                   |                     |
| ➤ <b>Warning:</b>             | Protect from humidity – Use and store at temperature above 18°C                   |                     |

Above mentioned figures represent the average values of our regular production; as such, they are not binding. Customer must verify through practical tests that product is fit for the use he intends it for and is responsible for any risk and damage caused by the use of the product. Above mentioned figures have a range of variation +/- 5% and may be changed at any moment for production needs or technical updates.

Test methods: AFERA