

TECHNICAL DATA SHEET: **732**

Validity date: **01 March 2015**

➤ Product Description:	Blue PE double-sided tape		
	CLEAR adhesive based on synthetic rubber with differential adhesion		
	Liner: 80g/m ² 2-side silicone white paper		
➤ Technical Data:	Total Thickness (adhesive + backing):	150 my	
	Rolling ball tack:	open side:	< 3,5 cm
		closed side:	< 3 cm
	Adhesion to steel:	open side:	2,7 N/cm
		closed side:	12 N/cm
	Static Shear:	open side:	> 24 h
		closed side:	> 300 h
Tensile strength:	17 N/cm		
Elongation at break:	280 %		
➤ Recommended Applications:	Recommended for lamination of various materials with a balanced adhesion (open side) and a high adhesion on closed side.		
	Recommended for temporary carpet mounting, where a good removability on one side (open) as well as an excellent adhesion on other side (closed) are requested		
	Recommended for sample-books manufacturing		
➤ Characteristics:	Recommended temperature during application: 20°C		
	Continuous use minimum and maximum temperature: from -10°C to 50°C		
➤ Warning:	Protect from humidity – Use and store at temperature above 18°C		
➤ Above mentioned technical data are valid also for the following versions:	J = jumbo		

Above mentioned figures represent the average values of our regular production; as such, they are not binding. Customer must verify through practical tests that product is fit for the use he intends it for and is responsible for any risk and damage caused by the use of the product. Above mentioned figures have a range of variation +/- 5% and may be changed at any moment for production needs or technical updates.

Test methods: AFERA - PSTC. rev. 1 Fabo