

## TECHNICAL DATA SHEET: 737

Validity date: 01 March 2015

Product Description:	Cotton lint double-sided tape	
	WHITE adhesive based on synthetic rubber	
	Liner: 80g/m <sup>2</sup> 2-side silicone yellow paper	
> Technical Data:	Total Thickness (adhesive + backing):	235 μm
	Adhesion to steel:	12 N/cm
	Rolling ball tack :	< 3 cm
	Tensile strength:	22 N/cm
	Elongation at break:	4 %
Recommended Applications:	Recommended for lamination of various materials	
	Recommended for splices and many other applications	
	Recommended for sample-books manufacturing	
Characteristics:	Recommended temperature during application: 20°C	
	Continuous use minimum and maximum temperature: from -10°C to 50°C	
Warning:	Protect from humidity – Use and store at temperature above 18°C	
Above mentioned technical data are valid also for the following versions:	<b>J</b> = jumbo	

Above mentioned figures represent the average values of our regular production; as such, they are not binding. Customer must verify through practical tests that product is fit for the use he intends it for and is responsible for any risk and damage caused by the use of the product. Above mentioned figures have a range of variation +/- 5% and may be changed at any moment for production needs or technical updates.

Test methods: AFERA - PSTC. rev. 1 Fabo