

# TECHNICAL DATA SHEET: **760HM**

Validity date: **01 March 2015**

➤ <b>Product Description:</b>	Non-woven double-sided tape	
	Hot melt adhesive	
	Liner: 80g/m <sup>2</sup> 2-side silicone brown paper	
➤ <b>Technical Data:</b>	Total Thickness (adhesive + backing):	90 μm
	Adhesion to steel:	9 N/cm
	Rolling ball tack :	< 3 cm
	Static shear :	130 h
	Tensile strength:	15 N/cm
	Elongation at break:	5 %
➤ <b>Recommended Applications:</b>	Lamination of various materials, paper mounting	
	Lamination of expanded materials, for foot-wear and leather goods	
➤ <b>Characteristics:</b>	Recommended temperature during application: 20°C	
	Continuous use minimum and maximum temperature: from -10°C to 50°C	
➤ <b>Warning:</b>	Protect from humidity – Use and store at temperature above 18°C	
➤ <b>Above mentioned technical data are valid also for the following versions:</b>	J = jumbo	

Above mentioned figures represent the average values of our regular production; as such, they are not binding. Customer must verify through practical tests that product is fit for the use he intends it for and is responsible for any risk and damage caused by the use of the product. Above mentioned figures have a range of variation +/- 5% and may be changed at any moment for production needs or technical updates.

Test methods: AFERA - PSTC. rev. 1 Fabo