






PRE-PRINTED NO NOISE ADHESIVE TAPE FOR HEAVY PACKAGING

PRODUCT DESCRIPTION


Pre-printed no noise adhesive tape made with water-based acrylic adhesive. The sandwich flexographic printing technology allows to obtain a high definition print quality. The increased thickness of the support and the high adhesive weight are suitable for closing heavy packages with manual dispensers or automatic carton sealing machines.



FEATURES

-  No noise unwinding
-  Solvent free
-  High definition printing
-  Increased thickness
-  Super adhesive

MAIN APPLICATIONS

-     Heavy weight box sealing
-  Manual dispensers
-  Automatic carton sealing machines




BACKING MATERIAL

BIAXIALLY ORIENTED
POLYPROPYLENE

AVAILABLE VERSIONS

C = colored

COLOURS

-  BROWN
-  WHITE
-  TRANSPARENT

TYPE OF ADHESIVE

WATER BASED ACRYLIC

TECHNICAL DATA	Metric	Values	Test method
Backing thickness	µm	35	AFERA 5006
Total thickness	µm	63	AFERA 5006
Adhesion to steel	N/cm	2.8	AFERA 5001
Tensile strength	N/cm	55	AFERA 5004
Elongation at break	%	160	AFERA 5004

Technical Informations, storage and product use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and away from direct light. The storage temperature must be between 15° and 30° C and the relative humidity between 40 and 60%. For storage temperatures other than those indicated, recondition the product to the levels described above. The technical data shown in the data sheets are the average of the analyzes obtained on normal production. Aging can determine the variation of some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data shown are reported with a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

Fabo spa declines all responsibility for direct damage and for the consequences deriving from improper use of the product. It is advisable to check the conformity of the product in relation to the specific conditions of use.

Rev.01_01/03/2023