

# TECHNICAL DATA SHEET

# ITEM CODE 248SF

# EASY UNWINDING ADHESIVE TAPE FOR HEAVY WEIGHT PACKAGING

### PRODUCT DESCRIPTION

Acrylic adhesive tape with solvent-free water-based adhesive featuring easy roll unwinding. The increased thickness of the backing and the high adhesive weight are suitable for heavy weight box sealing with manual dispensers or automatic carton sealing machines.



#### **FEATURES**



Noisy unwinding



Easy roll unwinding



Increased thickness



**UV** resistant

Solvent free



Super adhesive

### **MAIN APPLICATIONS**









Heavy weight box sealing



Manual dispensers



Automatic carton sealing machines

# **BACKING MATERIAL**

BIAXIALLY ORIENTED POLYPROPYLENE

**AVAILABLE VERSIONS** 

J = jumbo

#### **COLOURS**



BROWN



WHITE



TRANSPARENT

## **TYPE OF ADHESIVE**

WATER BASED ACRYLIC

TECHNICAL DATA	Metric	Values	Test method
Backing thickness	μm	35	AFERA 5006
Total thickness	μm	63	AFERA 5006
Adhesion to steel	N/cm	2.8	AFERA 5001
Tensile strength	N/cm	55	AFERA 5004
Elongation at break	%	160	AFERA 5004

#### Technical Informations, storage and product use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and away from direct light. The storage temperature must be between 15° and 30° C and the relative humidity between 40 and 60%. For storage temperatures other than those indicated, recondition the product to the levels described above. The technical data shown in the data sheets are the average of the analyzes obtained on normal production. Aging can determine the variation of some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data shown are reported with a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

Fabo spa declines all responsibility for direct damage and for the consequences deriving from improper use of the product. It is advisable to check the conformity of the product in relation to the specific conditions of use.

Rev.01\_01/03/2023



