

# **TECHNICAL DATA SHEET**

**ITEM CODE** 

250D

# **HIGH THICKNESS BACK PRINTED ADHESIVE TAPE**

## **PRODUCT DESCRIPTION**

Packaging tape with solvent-free water-based acrylic adhesive, printed on the back. The increased thickness of the backing guarantees a high strength packaging. Suitable for heavy weight box sealing with manual dispensers. Possibility of customization up to three colors.



## **FEATURES**



No noise unwinding



Increased thickness

## **MAIN APPLICATIONS**









Heavy weight box sealing



Manual dispensers

PRINTED

Back printed

Solvent free

## **BACKING MATERIAL**

BIAXIALLY ORIENTED POLYPROPYLENE

**TYPE OF ADHESIVE** 

WATER BASED ACRYLIC

## **AVAILABLE VERSIONS**

## **COLOURS**

**BROWN** 

C

WHITE



**TRANSPARENT** 

TECHNICAL DATA	Metric	Values	Test method
Backing thickness	μm	50	AFERA 5006
Total thickness	μm	70	AFERA 5006
Adhesion to steel	N/cm	2.4	AFERA 5001
Tensile strength	N/cm	65	AFERA 5004
Elongation at break	%	170	AFERA 5004

### Technical Informations, storage and product use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and away from direct light. The storage temperature must be between 15° and 30° C and the relative humidity between 40 and 60%. For storage temperatures other than those indicated, recondition the product to the levels described above. The technical data shown in the data sheets are the average of the analyzes obtained on normal production. Aging can determine the variation of some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data shown are reported with a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

Fabo spa declines all responsibility for direct damage and for the consequences deriving from improper use of the product. It is advisable to check the conformity of the product in relation to the specific conditions of use.

Rev.01 01/03/2023



