

BLACK HOT MELT STRAPPING TAPE

PRODUCT DESCRIPTION

Strapping tape made with a solvent free water-based acrylic adhesive. The high tensile strength of mono-oriented polypropylene backing guarantees excellent resistance to mechanical stress. Suitable for industrial packaging as general reinforcement, for bundling of various materials and palletization.



FEATURES



Noisy
unwinding



Increased backing
thickness



High tensile
strength

MAIN APPLICATIONS



Palletization



Bundling of materials, generic
reinforcement

BACKING MATERIAL

MONOAXIALLY ORIENTED
POLYPROPYLENE

AVAILABLE VERSIONS

J = jumbo

COLOURS

 BLACK

TYPE OF ADHESIVE

HOT MELT

TECHNICAL DATA	Metric	Value	Test Method
Backing thickness	µm	80	AFERA 5006
Total thickness	µm	97	AFERA 5006
Adhesion to steel	N/cm	5	AFERA 5001
Tensile strength	N/cm	250	AFERA 5004
Elongation at break	%	40	AFERA 5004

Technical Informations, storage and product use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and away from direct light. The storage temperature must be between 15° and 30° C and the relative humidity between 40 and 60%. For storage temperatures other than those indicated, recondition the product to the levels described above. The technical data shown in the data sheets are the average of the analyzes obtained on normal production. Aging can determine the variation of some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data shown are reported with a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

Fabo spa declines all responsibility for direct damage and for the consequences deriving from improper use of the product. It is advisable to check the conformity of the product in relation to the specific conditions of use.

Rev.01_01/03/2023