

## WASHI MASKING TAPE

### PRODUCT DESCRIPTION

Professional fine line masking tape having a smooth washi rice paper backing and a solvent free water based acrylic adhesive. Designed for indoor/outdoor high-precision masking applications. The backing material combined with a high tack acrylic adhesive allows perfect adhesion on various types of surfaces. Removable without adhesive residue transferring up to 8 weeks after application. Temperature resistance up to 100°C for 30 minutes.



### FEATURES



Solvent free



High precision



UV resistant



For internal / external use



Moisture resistant  
Backing



Removable /  
No residual

### MAIN APPLICATIONS



Professional masking in the painting and building industry

### BACKING MATERIAL

SMOOTH JAPANESE RICE PAPER

### AVAILABLE VERSIONS

J = jumbo

### COLOURS



### TYPE OF ADHESIVE

WATER BASED ACRYLIC

TECHNICAL DATA	Metric	Value	Test Method
Backing weight	g/m <sup>2</sup>	48	AFERA 5006
Total thickness	µm	95	AFERA 5006
Adhesion to steel	N/cm	1.5	AFERA 5001
Tensile strength	N/cm	30	AFERA 5004
Elongation at break	%	5	AFERA 5004

#### Technical Informations, storage and product use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and away from direct light. The storage temperature must be between 15° and 30° C and the relative humidity between 40 and 60%. For storage temperatures other than those indicated, recondition the product to the levels described above. The technical data shown in the data sheets are the average of the analyzes obtained on normal production. Aging can determine the variation of some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data shown are reported with a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

Fabo spa declines all responsibility for direct damage and for the consequences deriving from improper use of the product. It is advisable to check the conformity of the product in relation to the specific conditions of use.

Rev.01\_01/03/2023