

TECHNICAL DATA SHEET

ITEM CODE 910P

PRE-PRINTED PROTECTIVE ADHESIVE TAPE

PRODUCT DESCRIPTION

Pre-printed protective adhesive tape with solvent-free water-based acrylic adhesive and polyethylene film. The high thickness of the backing is suitable to cover various surfaces, protecting them from bumps and scratches during processing. The tape does not tear easily even in case of perforation. The tape can also be used for bundling, splicing, where good adhesion is required.



FEATURES



Noisy unwinding

Solvent free



Extendable backing



High definition printing

MAIN APPLICATIONS



Protective



Bundling

BACKING MATERIAL

AVAILABLE VERSIONS

COLOURS

LOW DENSITY POLYETHYLENE

J = jumbo



TYPE OF ADHESIVE

WATER BASED ACRYLIC

TECHNICAL DATA	Metric	Value	Test Method
Backing thickness	μm	100	AFERA 5006
Total thickness	μm	128	AFERA 5006
Adhesion to steel	N/cm	2.8	AFERA 5001
Tensile strength	N/cm	30	AFERA 5004
Elongation at break	%	>200	AFERA 5004

Technical Informations, storage and product use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and away from direct light. The storage temperature must be between 15° and 30° C and the relative humidity between 40 and 60%. For storage temperatures other than those indicated, recondition the product to the levels described above. The technical data shown in the data sheets are the average of the analyzes obtained on normal production. Aging can determine the variation of some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data shown are reported with a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

Fabo spa declines all responsibility for direct damage and for the consequences deriving from improper use of the product. It is advisable to check the conformity of the product in relation to the specific conditions of use.

Rev.01_01/03/2023



