

REMOVABLE PROTECTIVE ACRYLIC ADHESIVE TAPE

PRODUCT DESCRIPTION

Removable protective adhesive tape with solvent-free water-based acrylic adhesive and polyethylene film. Suitable in the applications where a good adhesion and easy removal are required without adhesive transferring. The high thickness of the backing allows to cover various surfaces, protecting them from bumps and scratches during processing or transport. The tape does not tear easily even in case of perforation.



FEATURES



Noisy
unwinding



Extendable
backing



Solvent free



UV resistant

MAIN APPLICATIONS



Protective



Residue-free removal

BACKING MATERIAL

LOW DENSITY POLYETHYLENE

AVAILABLE VERSIONS

J = jumbo

COLOURS



TRANSPARENT

TYPE OF ADHESIVE

REMOVABLE WATER BASED ACRYLIC

TECHNICAL DATA	Metric	Value	Test Method
Backing thickness	µm	100	AFERA 5006
Total thickness	µm	128	AFERA 5006
Adhesion to steel	N/cm	1.0	AFERA 5001
Tensile strength	N/cm	30	AFERA 5004
Elongation at break	%	>200	AFERA 5004

Technical Informations, storage and product use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and away from direct light. The storage temperature must be between 15° and 30° C and the relative humidity between 40 and 60%. For storage temperatures other than those indicated, recondition the product to the levels described above. The technical data shown in the data sheets are the average of the analyzes obtained on normal production. Aging can determine the variation of some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data shown are reported with a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

Fabo spa declines all responsibility for direct damage and for the consequences deriving from improper use of the product. It is advisable to check the conformity of the product in relation to the specific conditions of use.

Rev.01_01/03/2023