

PRINTABLE FIBERGLASS REINFORCED BROWN KRAFT PAPER ADHESIVE TAPE

PRODUCT DESCRIPTION

Fiberglass reinforced brown kraft paper adhesive tape with water-activated corn or potato starch-based adhesive. Thanks to the strong grip on the cardboard, the tape becomes one with the packaging, working as a natural anti-tempering system. Can be recycled with the paper packaging. Printable on the back with water-based inks ready to use in one step.



FEATURES



Recyclable



Reinforced backing



Water Activated Tape



Printable on the back



Natural anti tampering

MAIN APPLICATION






Very heavy weight box sealing




Manual and automatic use



Ideal for e-commerce

BACKING MATERIAL

KRAFT PAPER REINFORCED WITH TRI-DIRECTIONAL GLASS FIBERS SCRIM

AVAILABLE VERSIONS

COLOURS



TYPE OF ADHESIVE

CORN OR POTATO STARCH

TECHNICAL DATA	Metric	Value	Test Method
Backing weight	g/m2	105	AFERA 5006
Total thickness	µm	180	AFERA 5006
Adhesion to steel	N/cm	n.d.	AFERA 5001
Tensile strength	N/cm	125	AFERA 5004
Elongation at break	%	2	AFERA 5004

Technical Informations, storage and product use

The product must be used within 6 months from the delivery date (3 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and away from direct light. The storage temperature must be between 15° and 30° C and the relative humidity between 40 and 60%. For storage temperatures other than those indicated, recondition the product to the levels described above. The technical data shown in the data sheets are the average of the analyzes obtained on normal production. Aging can determine the variation of some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data shown are reported with a tolerance of +/- 15% and may be modified at any time for production needs or technical updates.

Fabo spa declines all responsibility for direct damage and for the consequences deriving from improper use of the product. It is advisable to check the conformity of the product in relation to the specific conditions of use.

Rev.00_07/06/2024