

TECHNICAL DATA SHEET

ITEM CODE 620

NATURAL RUBBER MASKING TAPE

PRODUCT DESCRIPTION

Multi-purpose ivory creped paper tape with natural rubber based adhesive. Thanks to its versatility is suitable for general indoor masking applications. Can be used also for home/office do-it-yourself and light weight packaging. Thermal resistance up to 60°C for 30 minutes.



FEATURES



Indoor applications



Removable / No residual



Professional masking in the painting and building industry



Do it yourself

MAIN APPLICATIONS



Thermal resistance up to 60°C for 30 minutes

AVAILABLE VERSIONS

COLOURS

SATURATED CREPED PAPER

J = jumbo



IVORY

TYPE OF ADHESIVE

BACKING MATERIAL

NATURAL RUBBER

TECHNICAL DATA	Metric	Value	Test Method
Backing weight	g/m2	55	AFERA 5006
Total thickness	μm	125	AFERA 5006
Adhesion to steel	N/cm	2	AFERA 5001
Tensile strength	N/cm	30	AFERA 5004
Elongation at break	%	10	AFERA 5004

Technical Informations, storage and product use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and away from direct light. The storage temperature must be between 15° and 30° C and the relative humidity between 40 and 60%. For storage temperatures other than those indicated, recondition the product to the levels described above. The technical data shown in the data sheets are the average of the analyzes obtained on normal production. Aging can determine the variation of some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data shown are reported with a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

Fabo spa declines all responsibility for direct damage and for the consequences deriving from improper use of the product. It is advisable to check the conformity of the product in relation to the specific conditions of use.

Rev.02_11/12/2023



