

ACRYLIC SEMI-CREPED MASKING TAPE FOR SENSITIVE SURFACES

PRODUCT DESCRIPTION

Purple semi-creped paper masking tape for sensitive surfaces with water-based acrylic adhesive. The special adhesive formulation is suitable for indoor applications in which easy removal without adhesive transferring is required (up to 15 days). The water-repellent treatment of the paper allows the use with most types of paint, even water-based ones. Thermal resistance up to 80°C for one hour.



FEATURES



Solvent free



Ideal for sensitive surfaces



UV resistant



Removable /
No residual



Indoor applications

MAIN APPLICATIONS



Professional masking in the painting and building industry

BACKING MATERIAL

SATURATED SEMI-CREPED PAPER

AVAILABLE VERSIONS

J = jumbo

COLOURS



PURPLE

TYPE OF ADHESIVE

WATER BASED ACRYLIC

TECHNICAL DATA	Metric	Value	Test Method
Backing weight	g/m ²	55	AFERA 5006
Total thickness	µm	105	AFERA 5006
Adhesion to steel	N/cm	0,8	AFERA 5001
Tensile strength	N/cm	40	AFERA 5004
Elongation at break	%	8	AFERA 5004

Technical Informations, storage and product use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and away from direct light. The storage temperature must be between 15° and 30° C and the relative humidity between 40 and 60%. For storage temperatures other than those indicated, recondition the product to the levels described above. The technical data shown in the data sheets are the average of the analyzes obtained on normal production. Aging can determine the variation of some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data shown are reported with a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

Fabo spa declines all responsibility for direct damage and for the consequences deriving from improper use of the product. It is advisable to check the conformity of the product in relation to the specific conditions of use.

Rev.01_01/03/2023