TECHNICAL DATA SHEET

ITEM CODE 393PCR

HIGH THICKNESS 90% PCR POLYESTER BACKING HOT MELT ADHESIVE TAPE

PRODUCT DESCRIPTION

Hot melt adhesive tape made with a formulation based on synthetic rubbers and hydrocarbon resins. Characterized by a 23 micron polyester film with 90% post-consumer recycled content (PCR). Suitable for medium weight box sealing with manual dispensers or automatic carton sealing machines.



FEATURES

- Noisy unwinding
- Increased thickness
- Space saving
- Shipping fees optimization
- Processing time optimization

MAIN APPLICATIONS

- Medium weight box sealing
- Automatic carton sealing machines
- Manual dispensers

BACKING MATERIAL

90% POST-CONSUMER RECYCLED BIORIENTATED POLYESTER

TYPE OF ADHESIVE

HOT MELT

AVAILABLE VERSIONS

J = jumbo

COLOURS

- BROWN
- WHITE
- TRANSPARENT

TECHNICAL DATA	Metric	Values	Test method
Backing thickness	µm	23	AFERA 5006
Total thickness	µm	40	AFERA 5006
Adhesion to steel	N/cm	5	AFERA 5001
Tensile strength	N/cm	48	AFERA 5004
Elongation at break	%	95	AFERA 5004

Technical Informations, storage and product use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and away from direct light. The storage temperature must be between 15° and 30° C and the relative humidity between 40 and 60%. For storage temperatures other than those indicated, recondition the product to the levels described above. The technical data shown in the data sheets are the average of the analyzes obtained on normal production. Aging can determine the variation of some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data shown are reported with a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

Fabo spa declines all responsibility for direct damage and for the consequences deriving from improper use of the product. It is advisable to check the conformity of the product in relation to the specific conditions of use.

90% refers to the polyester backing only. Recycled content documented by third-party supplier certifications and partly attributed using the mass balance method: not guaranteed in each individual roll. Assessed by FABO S.p.A. according to ISO 14021:2026, valid from the revision date of this data sheet.

Rev.01_07/10/2026

Via Cecinese, 84-84/A
51036 Larciano (PT) Italia
P.IVA 00126020478
fabotape.com

T. +39 0573 84851
F. +39 0573 84109
E. fabo@fabotape.com